



Europäisches  
Patentamt

Eur pean  
Patent Offic

Office européen  
des brevets

J1040 U.S. PTO  
10/002013  
10/26/01

Bescheinigung

Certificate

Attestation

Die angehefteten Unterla-  
gen stimmen mit der  
ursprünglich eingereichten  
Fassung der auf dem näch-  
sten Blatt bezeichneten  
europäischen Patentanmel-  
dung überein.

The attached documents  
are exact copies of the  
European patent application  
described on the following  
page, as originally filed.

Les documents fixés à  
cette attestation sont  
conformes à la version  
initialement déposée de  
la demande de brevet  
européen spécifiée à la  
page suivante.

Patentanmeldung Nr. Patent application No. Demande de brevet n°

01108455.5

Der Präsident des Europäischen Patentamts;  
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets  
p.o.

I.L.C. HATTEN-HECKMAN

DEN HAAG, DEN  
THE HAGUE, 27/04/01  
LA HAYE, LE





**Blatt 2 d r Besch inigung  
Sheet 2 of the c rtificate  
Page 2 de l'attestation**

Anmeldung Nr.:  
Application no.:  
Demande n°:

01108455.5

Anmeldetag:  
Date of filing:  
Date de dépôt:

04/04/01

Anmelder:  
Applicant(s):  
Demandeur(s):  
**Agilent Technologies, Inc.**  
**Palo Alto, CA 94306**  
**UNITED STATES OF AMERICA**

Bezeichnung der Erfindung:  
Title of the invention:  
Titre de l'invention:  
**Scattering attenuator**

In Anspruch genommene Priorität(en) / Priority(ies) claimed / Priorité(s) revendiquée(s)

Staat:  
State:  
Pays:

Tag:  
Date:  
Date:

Aktenzeichen:  
File no.  
Numéro de dépôt:

Internationale Patentklassifikation:  
International Patent classification:  
Classification internationale des brevets:

/

Am Anmeldetag benannte Vertragsstaaten:  
Contracting states designated at date of filing: AT/BE/CH/CY/DE/DK/ES/FI/FR/GB/GR/IE/IT/LI/LU/MC/NL/PT/SE/TR  
Etats contractants désignés lors du dépôt:

Bemerkungen:  
Remarks:  
Remarques:



## SCATTERING ATTENUATOR

### BACKGROUND OF THE INVENTION

EPO - Munich  
24

04. April 2001

The present invention relates to optical attenuators.

- EP-A-55742 discloses an optical attenuator for attenuating the intensity of a light beam emerging from an optical fiber. The attenuator comprises a wedge-shaped attenuator disk made of an absorbing material and a transparent disk that is also wedge-shaped and fixed to the absorbing disk. For adjusting different attenuations, the attenuator disk together with the transparent disk are rotated around an axis, whereby the thickness of the absorbing material through which the beam passes and thus the attenuation of the beam can be varied continuously. The problem with this solution is that the high local power consumption in the absorbing disk, which leads to heating and eventually destruction on the absorbing disk. Moreover, the attenuation shows a dependency on the wavelength.
- US-A-5,015,057 discloses a polarization insensitive optical attenuator that uses a polymer-dispersed liquid crystal (PDLC) film to provide attenuation control over a wide range of attenuation values. This solution, however, is only applicable in a small temperature range, which renders necessary use of a temperature regulation. Additionally, such PDLC attenuators show a hysteretic behavior, which complicates the control of the attenuation. Moreover, it has been shown that polymers generally do not exhibit sufficient long-term stability due to aging effects. Finally, such PDLC attenuators are not applicable for attenuating high power optical beams.

### SUMMARY OF THE INVENTION

- It is an object of the invention to provide an improved optical attenuator for fiber-optical applications. The object is solved by the independent claims. Preferred embodiments are shown by the dependent claims.

According to invention, a substantially parallel optical input beam is directed onto a scattering element of an attenuator. The scattering element scatters the input beam into a range of scattering directions. A beam collecting device, such as a collecting lens, of the attenuator is arranged in the range of scattering directions, and collects a portion of the scattered light as an output beam into an output fiber. The attenuation of the output beam with respect to the input beam is thus dependent on the portion of the collected light relative to the input beam.

The invention thus allows providing optical attenuators for high-power applications. Further more, the wavelength dependency for the provided attenuation can be minimized by selecting the particle size and distribution. Finally, there is virtually no limitation for long-term stability, since heating and thus aging effects can be effectively avoided and the attenuation itself does virtually not depend on the temperature of the scattering material.

In a preferred embodiment, the attenuator is provided with a shielding casing, at least in the range of scattering directions, in order to protect persons and equipment from light beams exciting the attenuator and to shield an output fiber from ambient light

The scattering element is preferably provided with a varying scattering angle distribution in order to control the attenuation. This can be done e.g. in that a volume scattering element is provided having a wedge-shape as disclosed e.g. by the aforementioned EP-A-55742. This allows controlling the attenuation by means of the effective thickness of the scattering element in the optical path. The scattering element can be provided having disk shape or a longitudinal shape. In the former case, the attenuation can be varied by rotating the disk. In the latter case, the attenuation can be varied by moving the longitudinal scattering element e.g. perpendicular to the input beam.

In another embodiment, the varying scattering angle distribution of the scattering element is provided by a gradient of the density of the scattering

particles or by a varying surface scattering angle distribution created for example by chemical etching, photofabrication or sandblasting.

### BRIEF DESCRIPTION OF THE DRAWINGS

Other objects and many of the attendant advantages of the present invention will be readily appreciated and become better understood by reference to the following detailed description when considering in connection with the accompanied drawing.

Fig. 1 shows a preferred embodiment of an optical attenuator according to the present invention.

### 10 DETAILED DESCRIPTION OF THE INVENTION

In Fig. 1, an optical attenuator 10 is coupled between an input fiber 20 and an output fiber 30. An input light beam 40 from the input fiber 20 is directed via a first lens (or a system of lenses) 50 as a parallel input light beam 60 towards a scattering element 70 of the attenuator 10. The scattering element 70 scatters the parallel input light beam 60 into a range of scattering directions 80. A second lens (or lens system) 90 of the attenuator 10 is arranged to collect a portion of the scattered light, and focuses the collected portion as an output beam 100 into the output fiber 30.

To optimize the performance of the attenuator 10, it is important to choose an appropriate scattering element. For high power applications the scattering element 70 should be non-absorbing, which is not necessarily the case for low power applications where the scattering element 70 could be absorbing. Furthermore the wavelength performance can be optimized by selecting the right size or size distribution of the particles or surface structure of the scattering element 70. Finally the polarization dependent loss can be minimized by choosing a surface structure or distribution of particles in the volume which is either random or has a 4-fold symmetry under rotation.





04. April 2001

## CLAIMS:

1. An optical attenuator (10) for attenuating the intensity of an input light beam (40, 60), comprising

5 a scattering element (70) for scattering the input light beam (40, 60) into a range of scattering directions, and

a beam collecting device (90) arranged in the range of scattering directions for collecting a portion of the scattered light as an output beam (100).

- 10 2. The optical attenuator (10) of claim 1, wherein the attenuation of the output beam (100) with respect to the input light beam (40, 60) is dependent on the portion of the collected light relative to the range of scattering directions.

- 15 3. The optical attenuator (10) of claim 1 or 2, further comprising a beam distributor (50) for providing the input light beam (60) as a substantially parallel beam to the scattering element (70).

4. The optical attenuator (10) of claim 1 or any one of the claims 2-3, wherein the particle size and distribution is selected for minimizing wavelength dependency.

- 20 5. The optical attenuator (10) of claim 1 or any one of the claims 2-4, further comprising a shielding casing, at least in the range of scattering directions.

6. The optical attenuator (10) of claim 1 or any one of the claims 2-5, wherein the scattering element (70) is provided with a varying scattering angle distribution in order to control the attenuation.

- 25 7. The optical attenuator (10) of claim 6, wherein the scattering element (70) has a wedge-shape and/or the effective thickness of the scattering

element is varied in the optical path.

8. The optical attenuator (10) of any one of claims 6-7, further comprising a device for moving the scattering element (70) in order to vary the attenuation.

5 9. The optical attenuator (10) of claim 6 or any one of the claims 7-8, wherein the scattering element (70) comprises a gradient of density of scattering particles and/or a varying surface scattering angle distribution.

10. A method for attenuating the intensity of an input light beam (40, 60), comprising the steps of:

10 (a) scattering the input light beam (40, 60) into a range of scattering directions, and

(b) collecting a portion of the scattered light as an output beam (100).

ABSTRACT

An optical attenuator (10) for attenuating the intensity of an input light beam (40, 60) comprises a scattering element (70) for scattering the input light beam (40, 60) into a range of scattering directions. A beam collecting device (90) is  
5 arranged in the range of scattering directions for collecting a portion of the scattered light as an output beam (100).

[Fig. 1 for publication]






Fig.1

